



## Uncertainty Analysis for the Parameterization of Glycols

Kruger, Francois

*Publication date:*  
2017

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Kruger, F. (2017). *Uncertainty Analysis for the Parameterization of Glycols*. Poster session presented at 29th European Symposium on Applied Thermodynamics, Bucharest, Romania.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



## A review of the 4C association scheme for mono-ethylene glycol (MEG)

Francois Kruger

Supervised by: Nicolas von Solms & Georgios Kontogeorgis

### Background

- Collaboration between DTU-CERE and Statoil ASA
- Natural gas dehydration: Statoil Subsea Factory<sup>TM(1)</sup> and Gas-2-Pipe<sup>TM(2)</sup>
- Important Sales Gas specifications:
  - Hydrocarbon dew point: cricondenbar 105-110 bar
  - H<sub>2</sub>O dew point: 32 ppm
  - Glycol in the gas phase 8 l/MSm<sup>3</sup>




Figure 1: Planned workflow for the Subsea Processing Project

### Literature Review

#### CPA parameterization of glycols

- CPA<sup>(3)</sup> parameter sets<sup>(4)</sup> for glycols fitted to pure component DIPPR<sup>(5)</sup> correlations, with liquid-liquid equilibrium (LLE) selection criterion

#### Uncertainty analysis utilized in CPA model development

- Bootstrapping recently used<sup>(6)</sup> to for CPA parameter estimation of CO<sub>2</sub>
- Effect of using pseudo data was not specifically evaluated

#### Literature survey: data for systems of interest

- Binary data are relatively scarce in the open literature and often incongruent
- Single ternary data set (methane-water-MEG) available<sup>(7)</sup>
- CPA can model both phases (mixture parameters fitted CH<sub>4</sub> solubility data only)

### Methodology

#### Parameter evaluation and uncertainty analysis

1. Data selection: pure and multicomponent
2. Determine objective function for parameter estimation:

$$OF_{\min} \left( a_0, b_0, c_1, \frac{\varepsilon}{R}, \beta, k_{ij} \right) = w_i \sum \left| \frac{i_{\text{calc}} - i_{\text{exp}}}{i_{\text{exp}}} \right|^2$$
$$i \in [P_{\text{Sat}}, \rho, \text{TPx}, \text{TPy}]$$

3. Run optimization to obtain new parameters
4. Bootstrap: randomly sample (with replacement) from experimental data and refit parameters according to  $OF_{\min}$
5. Repeat Step #4 1500 times
6. Determine parameter distributions and confidence intervals
7. Evaluate performance versus literature

### Results and Discussion

#### Use of pure component experimental data versus pseudo data

- Accuracy of MEG liquid density prediction sacrificed by incorporating the LLE-criterion
- MEG vapour pressure data exhibits significantly higher variance than the DIPPR correlation suggests
- Bootstrapped parameter plots show high degree of correlation when fitting to DIPPR

#### Uncertainty analysis: new CPA-4C MEG parameters

- Literature parameters do not match well with bootstrapped mean parameter estimator
- Mean of the average absolute error and 95% confidence interval over 1500 optimization runs:

Table 1: Parameter confidence intervals and fitting errors for newly proposed MEG 4C parameters

	Parameter							Data fit error [% ARD]				
	$b_0$ [cm <sup>3</sup> /mol]	$\Gamma$ [K]	$c_1$	$\varepsilon/R$ [K]	$\beta$ 10 <sup>3</sup>	$k_{12}$	$k_{13}$	$P_{\text{Sat}}$	$\rho$	TPx <sub>12</sub>	TPx <sub>13</sub>	TPy <sub>13</sub>
Literature	51.40	2532	0.6744	2376	14.10	-0.105	0.1786 0.1340	1.96	2.44	4.80	5.51 17.2	35.1 28.8
This work*	50.22	2830	0.6804	2197	14.74	-0.1233	0.093	1.78	0.81	3.01	4.55	15.4
95% CI (lb)*	50.13	2827	0.6738	2183	14.71	-0.1283	0.087					
95% CI (ub)*	50.41	2849	0.6819	2198	14.82	-0.1215	0.094					




Figure 2: Selected parameter distribution (left) and correlation plots (right), showing confidence intervals developed from the bootstrap method

### Application for Simplified NG Dehydration Systems

#### Binary systems

- Improved correlation of the MEG entrained into CH<sub>4</sub>-rich phase
- Prediction is best at both high temperature and high pressure
- Low temperature anomalies may be due to experimental difficulties




Figure 3: Correlation of MEG vapour phase fraction in CH<sub>4</sub>




Figure 4: Ternary VLE predictions for MEG-H<sub>2</sub>O-CH<sub>4</sub> at 278K and 298K

#### Ternary systems

- Prediction for MEG entrainment is much improved
- CH<sub>4</sub> solubility in the liquid phase is underpredicted

### Conclusions

- Excess (unnoticed) parameter correlation avoided by using raw experimental data in optimization routines
- New MEG 4C parameters provide improved description for simplified natural gas dehydration applications
- Accurate prediction of all components in all phases remains challenging
- Discrepancies highlight need for further experimental data and model development

### Future Work

- Generation of new experimental data for additional model evaluation
- Apply uncertainty analysis to newly proposed association schemes
- Inclusion of tri-ethylene glycol (TEG) data and modelling
- Modelling of natural gas dehydration in Aspen

### Acknowledgement

The authors wish to thank Statoil for their financial support of this research, which is part of the CHIGP (Chemical in Gas Processing) project

References:  
1. Ramberg, R. M., Davies, S. R., Rogn, H. & Økland, O. Steps to the Subsea Factory. in OTC-24307-MS (Offshore Technology Conference, 2013). doi:10.4043/24307-MS  
2. Fredheim, A. O., Johnsen, C. G., Johannessen, E. & Kojen, G. P. Gas-2-Pipe<sup>TM</sup>: A Concept for Treating Gas to Rich Gas Quality in a Subsea or Unmanned Facility. in (Offshore Technology Conference, 2016). doi:10.4043/27147-MS  
3. Kontogeorgis, G. M., V. Yakoumis, I., Meijer, H., Hendriks, E. & Moorwood, T. Multicomponent phase equilibrium calculations for water-methanol-alkane mixtures. *Fluid Phase Equilibria* **158-160**, 201-209 (1999).  
4. Derawi, S. O., Michelsen, M. L., Kontogeorgis, G. M. & Stenby, E. H. Application of the CPA equation of state to glycol/hydrocarbons liquid-liquid equilibria. *Fluid Phase Equilibria* **209**, 163-184 (2003).  
5. Brigham Young University (BYU). *DIAPPR Professional - DIPPR Information and Data Evaluation Manager*. (2016).  
6. Bjørner, M. G., Sin, G. & Kontogeorgis, G. M. Uncertainty analysis of the CPA and a quadrupolar CPA equation of state - With emphasis on CO<sub>2</sub>. *Fluid Phase Equilibria* **414**, 29-47 (2016).  
7. Folas, G. K. et al. High-pressure vapor-liquid equilibria of systems containing ethylene glycol, water and methane: Experimental measurements and modeling. *Fluid Phase Equilibria* **251**, 52-58 (2007).